



### LED Panel 3.9 mm Indoor

The **B Led3** is the perfect partner for all “mid-class” rental and fixed install requirements. Due to its slim and easy to handle design the cabinet can be used for all indoor applications. With its small 3.9 mm pitch, lightweight construction and standard Neutrik connectors this cabinet can be installed by hanging or stacking in the most demanding environments like events, TV, congress, trade shows, etc. ■

### Features

Indoor use	Rear and front service
Lightweight	Easy to handle cabinet
LCD Status Display	Standard Neutrik connectors
Standard dimensions	Hanging and stacking possibilities
On-board calibration	

### Physical

Dimensions (WxHxD)	50 x 50 x 8,5 cm
Nett weight	7 kg
Flight case dimensions (10 pcs)	120 x 85 x 60 cm
Gross weight flight case (10 pcs)	115 kg

### Mounting options

Hanging	Hanging bracket 50 cm
	Hanging bracket 100 cm
Standing	Prolyte truss stacking
Wall	Wall mounting system

### Control

Novastar processing	<ul style="list-style-type: none"> <li>▪ Receiving card A4s</li> <li>▪ Advised controller:                             <ul style="list-style-type: none"> <li>▪ MCTRL 660</li> <li>▪ MCTRL 4K</li> </ul> </li> </ul>
---------------------	--

### Technical information

Input power	100 - 240V ~ 50/60Hz   Auto switching power supply
In/Link	Neutrik Powercon True1
Average power	260W/m <sup>2</sup>
Signal connection	Neutrik Ethercon CAT5A
Brightness	≥ 1200 nits
Pitch	3.91 mm indoor SMD