


## **SPECSHEET**



## 5 x 10W RGB Amber Matrix LED

Introducing the B 5, a revolutionary lighting fixture in the matrix category with 5x 10W RGB Amber LEDs. This line matrix is the first to feature removable frost filters, enhancing its versatility and application range. The distinct Amber LEDs produce a warm glow effect, setting it apart from conventional RGB units.

Designed for flexibility, the B 5 can be configured in various setups, including flown, stacked, or positioned horizontally or vertically. Its removable frost filters and sleek design make it ideal for indoor use, where it opens up new creative possibilities for lighting design.



## **Physical**

Dimensions (WxHxD):
Packaging dimensions (WxHxD):

Net weight: Gross weight:

Outer packaging gross weight: Outer packaging dimensions: 580 x 114 x 72 mm | 22.8 x 4.5 x 2.8 in 610 x 195 x 195 mm | 24 x 7.7 x 7.7 in

4.8 kg | 10.6 lb 6 kg | 13.2 lb

21 kg | 46.3 lbs (4 Pcs)

630 x 410 x 410 mm | 24.8 x 16.1 x 16.1 in (4 Pcs)

## **Mounting options**

Hanging:

Second suspension:

Standing:

Adjustable bracket with fixing knobs

1 x Eye on the back of the fixture to pass a safety wire or carabiner Interlocking slots & receivers - Arrayable with Luxibel B25



**Control** 

Menu control: 2.4"TFT display with 4x touch buttons

Control: DMX512, master/slave, master/slave DMX mode

In/Link: XLR 5/3-pin

DMX Mode: 1/4/7/18/20 channels

Dimming: 8-bit

Dimming curve 4 curves (Linear, Exponential, Logarithmic, S-curve)

Tilt locking system: Two sided tilt locking

**Optical** 

Beam angle: 45° Pixel controlled

Colours: RGB + Amber Strobe: 0 - 20 Hz

**Electrical** 

Fixture rated power: 50W

LED engine: 5 x 10W RGBA

Input power:  $100 - 240V \sim 50/60$ Hz | Auto switching power supply

In/Link: powerCONTRUE 1 | max. link current 10A

Power Factor: 0.95 LVI: n/a

**Environmental** 

Cooling: Electronic heat control

IP rating: IP20 Max. environment temperature: 40°

**Accessories** 

Included powerCON True 1, Frost filter (B 5), Locking key, Hanging bracket,

Optional n/a

